



ELMO PX-30/-10

PROFESSIONAL VISUALISER

THE ELMO IN PRACTICE



Conferences



Technical Meetings

The ELMO PX-30 is the best visualiser in the lineup for professional use.

The 4K resolution and a wide range of connectivity options mean the device can be integrated into advanced AV systems for larger conference rooms, allowing speakers to give the best possible visual presentations to their audience.

It is also perfect for technical meetings being held via TV conference. Participants can easily share 3D images that help them discuss the details of objectives, in high resolution.

The recording function is very useful in courtrooms where physical evidence is always critical.

The intuitive interface with a preview monitor is also very effective for use in seminars – leaving the speaker undistracted to give their best presentations.

The ELMO PX-10 is also available with Full HD resolution and RS-232C port.




Courtrooms



Seminars

OPTICS / RESOLUTION



- ✓ 4K camera with 12 mega-pixels CMOS image sensor (PX-30)
- ✓ Resolution up to 4K (PX-30)
- ✓ One-touch autofocus
- ✓ Real time transmission of live pictures – at up to 60 fps

OPERATION



- ✓ Large capture area – A3 possible
- ✓ Wide range of connectivity options (see specs overleaf)
- ✓ Up to 288x magnification
 - 12x optical zoom
 - 2x sensor zoom
 - 12x digital zoom
- ✓ Intuitive control through preview monitor
- ✓ Multilingual menu
- ✓ Adhesive magnetic surface for handwritten annotations included
- ✓ ELMO Interactive Toolbox (EIT) software available
- ✓ 5 years warranty



Model	PX-30	PX-10
Image pickup device	12 megapixel CMOS sensor	
Resolution	Up to 4K	Up to Full HD
Illumination	Built-in LED	
Focus range	WIDE: 5 cm - ∞, TELE: 20 cm - ∞	
Zoom	12x optical + 2x sensor + 12x digital = 288x	
Focus control	One-push / zoom sync	
Capture area	431 x 321 mm (4:3), portrait format A4 via HDMI, A3 possible	
LCD display	5" touch display (preview and control)	
HDMI output	HDMI1.4 compatible 3,840 × 2,160 @30 fps 1,920 × 1,080 @60 fps 1,280 × 720 @60 fps	HDMI1.4 compatible 1,920 × 1,080 @60 fps 1,280 × 720 @60 fps
VGA output	1,920 × 1,080 @60 fps 1,280 × 720 @60 fps	
USB output	USB 3.0 compatible UVC (image) compatible UHD (3,840 × 2,160 @30 fps) FHD (1,920 × 1,080 @60 fps)	USB 3.0 compatible UVC (image) compatible FHD (1,920 × 1,080 @60 fps)
USB terminals	USB 3.0 (type B): Image transmission, USB 2.0 (type A): USB flash drive & power, USB (type A): Power	
HDBaseT output	3,840 × 2,160 @30 *2 1,920 × 1,080 @60 *1 1,280 × 720 @60 *1 Max. length of ethernet cable: *1 = 100 m, *2 = 70 m	X
Input terminals	HDMI (type A) x2, VGA x1 Recording via HDMI possible / output from HDMI to VGA possible	
Recording / playback	SD card (photo and video), USB flash device, internal memory storage	
Formats used	Video: mp4 (HEVC/H.264,AAC) 4K@/30fps, 2K/@60/30fps, 1K/@30 fps Photos: jpg (JPEG)	Video: mp4 (HEVC/H.264,AAC) 2K@60/30fps,1K@30 fps Photos: jpg (JPEG)
Audio	Input: External microphone / HDMI audio, Output: Line Out / HDMI audio	
Presentation	Rotation (90° / 180°), freeze, mask, black-and-white	
External control	TCP/IP Control / RS-232C / USB / remote control	RS-232C / USB / remote control
Dimensions	W297 x D482 x H478 mm (set up), W297 x D482 x H133 mm (folded)	
Image Control	White balance / Flicker correction / Brightness, Contrast adjustment / Noise reduction / edge enhancement / Shading and Pixel defect correction / Distortion correction / High-quality resizing / Chromatic aberration correction	

CONTACT

ELMO Europe SAS -
Head Office - France
12, place de la Defense,
Maison de la Defense
92974, Paris La Defense

Tel: +33 (0)1 73 02 67 06
Fax: +33 (0)1 73 02 67 10
E-Mail: info@elmoeurope.com
Web: www.elmoeurope.com

ELMO Europe SAS Middle
East (Branch)
5WA-129, Dubai Airport
Free Zone
P.O. Box 371556, Dubai
United Arab Emirates

Tel: +971-(0)4-260-2390
MOB: +971 (56)477-3475
FAX: +971-(0)4-260-2392
Tariq@elmoeurope.com
www.elmoeurope.com