

3225 AF & 3215



..... The 3225 AF and 3215 are characterized by high level technology integrating Random Access, high light output, extreme compactness, ease of use and a total compatibility with most helical and rack-mount lenses and accessories existing on the market.

- Exceptional value for money
- TWIN 24V/250W lamps with rapid manual change (*model 3225 AF only*)
- Random Access via remote control
- Built-in timer and autoshow (*model 3225 AF only*)
- 6 pin DIN socket for CUT control
- Rapid slide tray homing to zero position
- 0,9 second slide change
- Microprocessor controlled
- Mechanical, electrical and thermal security (Independent fan motor)
- All the other advantages of the SIMDA projector range
- 5 motors
- Class II isolation
- Comply to European standards EN 55014, EN 55104, and EN 60336-2-56

 **SIMDA**
UNMATCHED QUALITY

3225 AF & 3215

3225 AF



3215



TWIN 24V/250W LAMPS WITH RAPID MANUAL CHANGE
(model 3225 AF only)

: All our lamps are of excellent quality but they can only blow when being used...i.e. during a show! With the rapid manual change, the problem is overcome by simply sliding the lamp change lever to the back-up lamp.

6 PIN DIN SOCKET FOR "CUT" FUNCTION

: This socket allows the projector to be controlled from any SIMDA remote control, such as CAD, IFR S/K, IFR 6, IFR 8, IFR 12, and from a 1000 Hz synchroniser.

AUTOSHOW AND TIMER
(model 3225 AF only)

: The autotimer provides programming of a preset interval time from 2 to 120 seconds between automatic slide changes. The autoshow returns the slide tray to zero when it senses a gap of two slides and then restarts automatically. These two modes are retained in the projector memory even after it has been switched off! This is an invaluable feature for all continuous applications such as showrooms, points of sale and exhibitions.

BUILT-IN REMOTE FOCUS
(model 3225 AF only)

: Simultaneous operation of the Focus button and the Forward or Reverse buttons provides fine focus control.

AUTOFOCUS MODEL 3225 AF (SIMDA PATENT)

: Autofocus system with manual override. The remote control can override the autofocus which is then reactivated after the next slide change.

RANDOM ACCESS

: Thanks to a number of our Remote Controls, the user can, in addition to normal functions, select any slide in the tray within 6 seconds.

N.S.N.L.
(model 3225 AF only)

: If there is no slide in the gate, there is no light on the screen, therefore avoiding the unpleasant "white screen".

TECHNICAL DATA

: Voltage selection : 230V
 (option : 115V).
 Size : H 124 x W 286 x L 330 mm
 (Height with slide tray : 170 mm). Weight : 7,1 Kg

